

Product Data Sheet

MAK PUMP

SAE Grade: 40

DESCRIPTION

This is specially developed to meet the engine oil requirements of agricultural pump sets.

PERFORMANCE BENEFITS

- Good thermo-oxidative stability
- High detergency, anti-wear and anti-corrosive properties

APPLICATIONS

This oil is recommended for agricultural pump sets, threshers, sugarcane harvesters / crushers etc.

PERFORMANCE LEVEL

- API CC
- IS 13656 : 2002 EDL 1
- US MIL-L-2104B

Characteristics	IS 1448	Typical Figures 40
Appearance	--	Clear & Bright
Colour, Visual Observation	--	Red
Density @15°C, gm/ml	P:16	0.8880
K.V at 100° C, cSt	P:25	14.4
Copper Corrosion @ 100° C for 3 hrs	P:15	1a
Flash Point, (COC), °C	P:69	222
Viscosity Index	P:56	96
Pour Point, °C	P:10	-8
Foaming Tendency / Stability: Qty. of foam in ml		
a) Sequence I	P:67	Nil / Nil
b) Sequence II		10 / Nil
c) Sequence III		Nil / Nil

Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Auto / 046 / Issue 1 / Oct, 2008