

## Product Data Sheet

# MAK PUMP

SAE Grade: 40

### DESCRIPTION

This is specially developed to meet the engine oil requirements of agricultural pump sets.

### PERFORMANCE BENEFITS

- Good thermo-oxidative stability
- High detergency, anti-wear and anti-corrosive properties

### APPLICATIONS

This oil is recommended for agricultural pump sets, threshers, sugarcane harvesters / crushers etc.

### PERFORMANCE LEVEL

- API CC
- IS 13656 : 2002 EDL 1
- US MIL-L-2104B

Characteristics	IS 1448	Typical Figures 40
Appearance	--	Clear & Bright
Colour, Visual Observation	--	Red
Density @15°C, gm/ml	P:16	0.8880
K.V at 100° C, cSt	P:25	14.4
Copper Corrosion @ 100° C for 3 hrs	P:15	1a
Flash Point, (COC), °C	P:69	222
Viscosity Index	P:56	96
Pour Point, °C	P:10	-8
Foaming Tendency / Stability: Qty. of foam in ml		
a) Sequence I	P:67	Nil / Nil
b) Sequence II		10 / Nil
c) Sequence III		Nil / Nil

### Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

**Bharat Petroleum Corporation Ltd.**

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z\_techservices@bharatpetroleum.in

Edition: R&D / Auto / 046 / Issue 1 / Oct, 2008