

## Product Data Sheet

# MAK BRAKE FLUID

### DESCRIPTION

It is premium synthetic fluid specially developed and approved for use in hydraulic breaking systems of all vehicles.

### PERFORMANCE BENEFITS

- Has a high reflux boiling point
- Good fluidity and stability even at low temperatures to make braking effective

### APPLICATIONS

This oils is recommended for use in both disc and drum brake systems of vehicles.

### PERFORMANCE LEVEL

- FMVSS-116 DOT-3
- IS 8654 : 2001
- SAE-J-1703

Characteristics	Requirement	Typical Figures
Appearance	Clear & Bright	Clear & Bright
Equilibrium Reflux Boiling point, (ERBP) °C, min.	205	215
Wet ERBP, °C, min.	140	152
KV, cSt at -40°C, max. at 100°C, min.	1500 1.5	1300 2.0
pH	7.0 to 11.5	8.2

### Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

**Bharat Petroleum Corporation Ltd.**

Technical Services

A<sup>1</sup> Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z\_techservices@bharatpetroleum.in

*Edition: R&D / Auto / 036 / Issue 1 / Oct, 2008*