

Product Data Sheet

MAK REDI KOOL

DESCRIPTION

This is specially formulated synthetic, environment friendly premixed ready to use radiator coolant.

PERFORMANCE BENEFITS

- This coolant dissipates heat efficiently
- Prevents coolant freeze-up and boil over
- Protects radiator and engine block from rust & corrosion

APPLICATIONS

It is recommended for use without dilution with water in mobile and stationary engines having closed loop coolant circulation systems.

PERFORMANCE LEVEL

- JIS K 2234-1994, Class II (LLC Type)
- IS 5759:2006

| Characteristics | requirements | Typical Figures |
|-----------------------------------|--------------|-----------------|
| Colour | Dark green | Dark green |
| Density at 20°C g/cm ³ | 1.050 min. | 1.062 |
| Boiling point, °C | 106 min. | 108 |
| pH | 7.5 to 11.0 | 8.04 |
| Water content, % wt. | 71.5 max. | 70.2 |

Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Auto / 035 / Issue 1 / Oct, 2008