

Product Data Sheet

MAK REDI KOOL

DESCRIPTION

This is specially formulated synthetic, environment friendly premixed ready to use radiator coolant.

PERFORMANCE BENEFITS

- This coolant dissipates heat efficiently
- Prevents coolant freeze-up and boil over
- Protects radiator and engine block from rust & corrosion

APPLICATIONS

It is recommended for use without dilution with water in mobile and stationary engines having closed loop coolant circulation systems.

PERFORMANCE LEVEL

- JIS K 2234-1994, Class II (LLC Type)
- IS 5759:2006

Characteristics	requirements	Typical Figures
Colour	Dark green	Dark green
Density at 20°C g/cm ³	1.050 min.	1.062
Boiling point, °C	106 min.	108
pH	7.5 to 11.0	8.04
Water content, % wt.	71.5 max.	70.2

Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services
 A' Installation, Sewree (East), Mumbai – 400 015
 Phone: 022-24176354, Fax: 022-24182511 / 24166512
 email: z_techservices@bharatpetroleum.in

Edition: R&D / Auto / 035 / Issue 1 / Oct, 2008