

## Product Data Sheet

# MAK SHOCK ABSORBER FLUID-1F

### DESCRIPTION

This is specially formulated fluid for use in latest design automotive shock absorbers.

### PERFORMANCE BENEFITS

- Ensures smoother ride by excellent dampening of shock loads
- Provides very high degree of chemical stability
- Good seal compatibility
- very low pour point which will enable its use over wide temperature range

### APPLICATIONS

These are approved by M/s Munjal Showa Ltd.

### PERFORMANCE LEVEL

- Proprietary brand

Characteristics	IS 1448	Typical Figures
Appearance	--	Clear & Bright
Colour, Visual Observation	--	Red
Density @15°C	P:16	0.9010
K.V at 40° C, cSt	P:25	35.5
Viscosity Index	P:56	106
Flash Point, (COC), °C	P:69	186
Pour Point, °C	P:10	<-42
Aniline point, °C	P:3	82.7
Foaming Tendency / Stability: Qty. of foam in ml		
a) Sequence I	P:67	10 / Nil
b) Sequence II		10 / Nil
c) Sequence III		10 / Nil

### Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

**Bharat Petroleum Corporation Ltd.**

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z\_techservices@bharatpetroleum.in

Edition: R&D / Auto / 040 / Issue 1 / Oct, 2008