

Product Data Sheet

MAK 2T

DESCRIPTION

It is a new generation semi-synthetic, extremely low smoke, environmentally friendly two stroke engine oil. Blended from highly refined mineral base oil & a special synthetic component, and fortified with finely balanced low ash additives. A specially selected diluent is added to ensure instantaneous self-mixing of oil with fuel.

APPLICATIONS

It is used for all types of 2 or 3 wheeler vehicles and outboard boats fitted with 2 stroke petrol engines / CNG gas.

For gear box application of 2 wheelers, use MAK MULTIGRADE 20W-40.

This oil received On-file status from JASO (Japanese Automotive Standards Organisation) 2-Cycle Oil Standards Implementation Panel for Gasoline Engine Performance Classification (JASO M 345).

PERFORMANCE BENEFITS

- Extremely low visible exhaust smoke levels
- Reduced spark plug fouling and exhaust system deposits
- Excellent lubrication under all working conditions, thereby, leading to longer engine life, increased fuel economy, reduced maintenance cost, and above all, reduced environmental pollution

PERFORMANCE LEVEL

- JASO FC
- API TC
- ISO GC
- T-SL4 Category of IS 14234 (part 1) : 2002

Characteristics	IS 1448	Typical Figures
Appearance	--	Clear & Bright
Colour, Visual Observation	--	Orange
Density @15°C	P:16	0.8797
K.V at 100° C, cSt	P:25	8.4
Copper Corrosion @ 100° C for 3 hrs	P:15	1a
Flash Point, (PMCC), °C	P:69	94

Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Auto / 001 / Issue 1 / Oct, 2008