

## Product Data Sheet

# MAK ELITE

SAE Grade: 15W-40

### DESCRIPTION

This is a premium quality multigrade petrol engine oils specially developed for use in new generation passenger cars whose higher speeds, loads and temperatures call for an engine oil having better thermo-oxidative stability and anti-wear property. This oil is manufactured from superior quality high viscosity index base oils fortified with selected additives & VI Improvers.

### PERFORMANCE BENEFITS

- Very good oxidation stability and added protection against wear, engine deposits, rust & corrosion
- High degree of engine cleanliness
- Ensure smooth running of engine in all climatic conditions
- Longer engine life and oil drain interval
- Compatible with catalytic converters

### APPLICATIONS

They are recommended for use in latest generation petrol engine cars like Hyundai Santro, Daewoo, Matiz & Cielo, Fiat Uno, Maruti Esteem.

### PERFORMANCE LEVEL

- API SJ / CF
- IS 13656 : 2002 Type EPL3

Characteristics	IS 1448	Typical Figures 15W-40
Appearance	--	Clear & Bright
Colour, Visual Observation	--	Red
Density @15°C, gm/ml	P:16	0.8750
K.V at 100° C, cSt	P:25	14.3
Copper Corrosion @ 100° C for 3 hrs	P:15	1a
Flash Point, (COC), °C	P:69	244
Viscosity Index	P:56	136
Pour Point, °C	P:10	-27
Foaming Tendency / Stability: Qty. of foam in ml		
a) Sequence I	P:67	Nil / Nil
b) Sequence II		10 / Nil
c) Sequence III		Nil / Nil

### Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

**Bharat Petroleum Corporation Ltd.**

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z\_techservices@bharatpetroleum.in

Edition: R&D / Auto / 007 / Issue 1 / Oct, 2008