

## Product Data Sheet

# MAK SUPREME

SAE Grade: 10W-30

### DESCRIPTION

This is supreme quality multigrade petrol engine oil exclusively developed for use in ultra-modern petrol cars to meet stringent lubrication requirements of Hi-tech engines. It is formulated using superior quality high viscosity index base oils and the state-of-the-art additive technology ensures maximum realization of engine power.

### PERFORMANCE BENEFITS

- Excellent protection of engine components against wear, rust and corrosion
- Less thickening of oil due to its excellent thermo-oxidative stability
- Ensure smooth running of engine in all climatic conditions
- Enhanced catalytic converter life due to improved harmonization

### APPLICATIONS

This is recommended for ultra-modern petrol cars that are powered by engines with advanced technology.

### PERFORMANCE LEVEL

- API SM

Characteristics	IS 1448	Typical Figures 10W-30
Appearance	--	Clear & Bright
Colour, Visual Observation	--	Brown
Density @15°C, gm/ml	P:16	0.8750
K.V at 100° C, cSt	P:25	10.42
Copper Corrosion @ 100° C for 3 hrs	P:15	1a
Flash Point, (COC), °C	P:69	220
Viscosity Index	P:56	141
Pour Point, °C	P:10	-30
Foaming Tendency / Stability: Qty. of foam in ml		
a) Sequence I	P:67	Nil / Nil
b) Sequence II		10 / Nil
c) Sequence III		Nil / Nil

### Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

**Bharat Petroleum Corporation Ltd.**

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z\_techservices@bharatpetroleum.in

Edition: R&D / Auto / 008 / Issue 1 / Oct, 2008