

Product Data Sheet

MAK LANTHAX EP GREASE

NLGI Grade: 00, 0, 1 & 2

DESCRIPTION

It is premium quality lithium based grease containing extreme pressure additives. These are suitable for heavy-duty roller & plain bearings, and for situations warranting a use of extreme pressure grease, particularly to those subjected to shock loads at temperatures up to about 130°C.

PERFORMANCE BENEFITS

- Contains extreme pressure additives which confer excellent shear stability and high load carrying ability

APPLICATIONS

This oil is recommended for all plain & roller bearings in equipments operating under severe shock loading conditions and temperatures up to about 130°C. NLGI 1 grade is used in centralized grease lubrication system.

PERFORMANCE LEVEL

- IS 7623 : 1993 EP Type [Reaffirmed 2001]
- IPSS : 1-09-005-99

Characteristics	IS 1448	Typical Figures			
		00	0	1	2
Type of thickener	--	Lithium	Lithium	Lithium	Lithium
Consistency of the worked grease at 25°C					
a) 60 double strokes		415	368	325	280
b) 100000 strokes	P:60	--	--	25 units	25 units
Drop point, °C	P:52	140	160	184	186
Copper Strip Corrosion Test @ 100°C for 24 hrs.	P:51	Negative	Negative	Negative	Negative

Health and Safety

These greases are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A¹ Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Grease / 007 / Issue 1 / Oct, 2008