

Product Data Sheet

MAK MOLYGREASE

NLGI GRADE : 2

DESCRIPTION

This is Lithium base, multipurpose grease fortified with 3% molybdenum disulphide for protection of moving parts under severe shock load conditions and resists water washout.

PERFORMANCE BENEFITS

- It can withstand shock loading conditions and gives good performance.
- It provides long service life.

APPLICATIONS

It is recommended in certain automobile parts lubrication where shock loading occurs.

Also recommended for the industrial applications where lithium base grease required with 3% molybdenum disulphide

PERFORMANCE LEVEL

- IS 12203:1999(Grade 3)

Characteristics	IS 1448	Typical Figures
Consistency of the worked grease at 25°C	P:60	275
Drop point, °C	P:52	190
Thermal Stability, % wt. loss, max	P:89	3
Resistance to water wash-out at 80°C, % wt loss, max	P:90	4
Molybdenum disulphide content, % wt, min	P:58	3

Health and Safety

This grease is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Grease / 003 / Issue 1 / Oct, 2008