

Product Data Sheet

MAK UNIVEX CD

NLGI Grade: 1

DESCRIPTION
 This is calcium (lime) based grease specially designed for chassis lubrication of automotive vehicles.

APPLICATIONS
 This grease is recommended for chassis lubrication of all types of automotive vehicles including commercial vehicles, tractors and other heavy-duty equipment.

PERFORMANCE BENEFITS

- Exhibits good water resistance and adhesive characteristics

PERFORMANCE LEVEL

- IS 506 :1993 Grade 1

Characteristics	IS 1448	Typical figures
Consistency of the worked grease at 25°C	P:60	320
Drop point, °C	P:52	100
Free Organic Acidity (as oleic acid), % by mass, max.	P:53	0.2
Free alkanity (as Ca(OH) ₂), % by mass	P:53	0.1
Copper Strip Corrosion Test @ 75°C for 24 hrs.	P:51	Negative

Health and Safety

This grease is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.
 Technical Services
 A' Installation, Sewree (East), Mumbai – 400 015
 Phone: 022-24176354, Fax: 022-24182511 / 24166512
 email: z_techservices@bharatpetroleum.in

Edition: R&D / Grease / 021 / Issue 1 / Oct, 2008