

Product Data Sheet

MAK WB GREASE SPECIAL

NLGI Grade: 2

DESCRIPTION
This is a sodium (soda) based grease.

PERFORMANCE BENEFITS

- Very high melting point

APPLICATIONS
This grease is recommended for lubrication of wheel bearings, universal joints and ball & roller bearings of electrical equipment of automotive vehicles.

PERFORMANCE LEVEL

- IS 10647 :1983

Characteristics	IS 1448	Typical figures
Consistency of the worked grease at 25°C 60 strokes	P:60	265
Drop point, °C	P:52	184
Free Organic Acidity (as oleic acid), % by mass, max.	P:53	Nil
Free alkanity (as LiOH), % by mass	P:53	0.15
Free alkanity (as NaOH), % by mass	P:53	0.15
Copper Strip Corrosion Test @ 100°C for 24 hrs.	P:51	Negative

Health and Safety

This grease is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.
 Technical Services
 A' Installation, Sewree (East), Mumbai – 400 015
 Phone: 022-24176354, Fax: 022-24182511 / 24166512
 email: z_techservices@bharatpetroleum.in

Edition: R&D / Grease / 023 / Issue 1 / Oct, 2008