

## Product Data Sheet

# MAK TURGONA

SAE GRADE: 30, 40 & 50

### DESCRIPTION

These are highly refined straight mineral oils with good oxidation stability.

### PERFORMANCE BENEFITS

- Excellent oxidation stability

### APPLICATIONS

These oils are recommended for reciprocating and vane type air compressors for which straight mineral oils are suitable.

### PERFORMANCE LEVEL

- Proprietary grades

Characteristics	IS 1448	Typical Figures		
		30	40	50
Appearance	--	Clear & Bright	Clear & Bright	Clear & Bright
Density @15°C	P: 16	0.8881	0.8919	0.8999
K.V at 100° C, cSt	P: 25	11.2	14.3	18.7
Viscosity Index	P: 56	96	95	95
Pour Point, °C	P: 10	-9	-6	-6
Flash Point, (COC), °C	P: 69	230	242	254
Copper strip Corrosion @ 100 °C	P: 15	1a	1a	1a

### Health and Safety

These oils are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

**Bharat Petroleum Corporation Ltd.**

Technical Services

A<sup>1</sup> Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z\_techservices@bharatpetroleum.in

*Edition: R&D / Indl / 011 / Issue 1 / Oct, 2008*