

## Product Data Sheet

# MAK CABOL 32 TF

### DESCRIPTION

This is premium quality oil having exceptional properties for a long and trouble free life in the system.

### PERFORMANCE BENEFITS

- Exceptionally good oxidation and thermal stability
- Shows low volatility

### APPLICATIONS

This oil is ideally suited for enclosed heat transfer system up to 280°C.

### PERFORMANCE LEVEL

- Proprietary grade

Characteristics	IS 1448	Typical Figures
Appearance	--	Light brown clear fluid
Density at 15° C	P:16	0.8647
K.V at 100° C, cSt	P:25	4.9
Viscosity Index	P:56	105
Pour Point, °C	P:10	-18
Flash Point, (COC), °C	P:69	226
Copper Strip Corrosion Test at 100°C for 3 hrs.	P:15	1a

### Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

**Bharat Petroleum Corporation Ltd.**

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z\_techservices@bharatpetroleum.in

*Edition: R&D / Indl / 029 / Issue 1 / Oct, 2008*