

## Product Data Sheet

# MAK FREEZOL J

ISO VG: 100

### DESCRIPTION

This is specially blended compounded oil of relatively low viscosity from Naphthenic type base oil.

### PERFORMANCE BENEFITS

- Better lubricity

### APPLICATIONS

It is recommended for cylinder lubrication of reciprocating compressors where moisture conditions warrant the use of compounded oil.

### PERFORMANCE LEVEL

- Proprietary grade

Characteristics	IS 1448	Typical Figures
Appearance	--	Bright & Clear fluid
Density at 15°C	P:16	0.8976
K.V at 40° C, cSt	P:25	100.1
Viscosity Index	P:56	58
Pour Point, °C	P:10	-27
Flash Point, (COC), °C	P:69	216
Copper Strip Corrosion Test at 100°C for 3 hrs.	P:15	1a

### Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

**Bharat Petroleum Corporation Ltd.**

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z\_techservices@bharatpetroleum.in

Edition: R&D / Indl / 108 / Issue 1 / Oct, 2008