

Product Data Sheet

MAK HYDROL HLP

ISO VG: 22, 32, 46, 68, 100 & 150

DESCRIPTION

These are premium grade extra heavy duty anti-wear oils with outstanding thermal stability and high FZG rating.

APPLICATIONS

These are recommended for high pressure hydraulic systems and also for power transmission in systems operating at high speeds, loads and temperatures. These are suitable for lubrication of pumps and industrial hydraulic machinery operating under heavy loads. These are specially recommended for sophisticated high performance Electrohydraulic or Numerically Controlled systems.

MAK HYDROL HLP 32 is approved by –

- M/s Voith (I) Ltd., Hyderabad for use in voith variable speed and hydraulic coupling
- M/s BHEL for use in boiler feed pumps, booster pumps and drive motor bearings

PERFORMANCE BENEFITS

- High thermal stability and excellent compatibility with seals
- They provide trouble-free service and have found to be far superior than other anti-wear hydraulic oils
- Good oxidation stability
- Possesses high FZG rating

PERFORMANCE LEVEL

- 11th FLS of FZG – Niemann EP test
- IS 11656 : 1986 [Reaffirmed March, 2002]
- DIN 51 524 Part II HL P Type
- Denison HF-0 & HF-2
- Vickers 1-286-S
- US Steel 127
- Cincinnati Milacron P-70

Our grades meet above specifications for the respective viscosity grades.

Characteristics	IS 1448	Typical Figures		
		22	32	46
Appearance	--	Clear fluid	Clear fluid	Clear fluid
Density at 15° C	P:16	0.8490	0.8513	0.8561
K.V at 40° C, cSt	P:25	22.9	32.6	46.1
Viscosity Index	P:56	104	103	103
Pour Point, °C	P:10	-21	-21	-21
Flash Point, (COC), °C	P:69	200	210	244
Copper Strip Corrosion Test at 100°C for 3 hrs.	P:15	1a	1a	1a
Foaming Characteristics/Stability	P:67	Nil	Nil	Nil
a) Sequence I				
b) Sequence II				
c) Sequence III		Nil	Nil	Nil

Product Data Sheet

Characteristics	IS 1448	Typical Figures		
		68	100	150
Appearance	--	Clear fluid	Clear fluid	Clear fluid
Density at 15° C	P:16	0.8598	0.8644	0.8705
K.V at 40° C, cSt	P:25	68.3	100.5	150.7
Viscosity Index	P:56	102	101	99
Pour Point, °C	P:10	-18	-18	-18
Flash Point, (COC), °C	P:69	248	256	260
Copper Strip Corrosion Test at 100°C for 3 hrs.	P:15	1a	1a	1a
Foaming Characteristics/Stability	P:67			
a) Sequence I		Nil	Nil	Nil
b) Sequence II		Nil	Nil	Nil
c) Sequence III		Nil	Nil	Nil

Health and Safety

These oils are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Indl / 037 / Issue 1 / Oct, 2008