

Product Data Sheet

MAK HYDROL TQ 32

DESCRIPTION

This is a specially developed hydraulic transmission fluid fortified with high performance additives that incorporates excellent properties for catering to the severe demands of gears and bearings in transmission.

PERFORMANCE BENEFITS

- Good anti-wear and anti-rust properties
- Excellent extreme pressure properties
- Useful in low temperature operating conditions

APPLICATIONS

It is recommended for use in Turbo Transmission systems, Torque Converters & Fluid Couplings.

PERFORMANCE LEVEL

- 3.90-8A of Voith Getreibe, Germany

Characteristics	IS 1448	Typical Figures
Density at 15° C	P:16	0.856
K.V at 40° C, cSt	P:25	32.5
Viscosity Index	P:56	118
Pour Point, °C	P:10	-45
Flash Point, (COC), °C	P:69	234
TAN, mg KOH / g	--	0.22
Color No	P:12	L 0.5

Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services
 A' Installation, Sewree (East), Mumbai – 400 015
 Phone: 022-24176354, Fax: 022-24182511 / 24166512
 email: z_techservices@bharatpetroleum.in

Edition: R&D / Indl / 046 / Issue 1 / Oct, 2008