

# Product Data Sheet

## MAK UNIVEX CD

NLGI Grade: 1

**DESCRIPTION**  
 This is calcium (lime) based grease specially designed for chassis lubrication of automotive vehicles.

**PERFORMANCE BENEFITS**

- Exhibits good water resistance and adhesive characteristics

**APPLICATIONS**  
 This grease is recommended for chassis lubrication of all types of automotive vehicles including commercial vehicles, tractors and other heavy-duty equipment.

**PERFORMANCE LEVEL**

- IS 506 :1993 Grade 1

Characteristics	IS 1448	Typical figures
Consistency of the worked grease at 25°C	P:60	320
Drop point, °C	P:52	100
Free Organic Acidity (as oleic acid), % by mass, max.	P:53	0.2
Free alkanity (as Ca(OH) <sub>2</sub> ), % by mass	P:53	0.1
Copper Strip Corrosion Test @ 75°C for 24 hrs.	P:51	Negative

**Health and Safety**  
 This grease is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

**Bharat Petroleum Corporation Ltd.**  
 Technical Services  
 A' Installation, Sewree (East), Mumbai – 400 015  
 Phone: 022-24176354, Fax: 022-24182511 / 24166512  
 email: z\_techservices@bharatpetroleum.in

*Edition: R&D / Grease / 021 / Issue 1 / Oct, 2008*