

# Product Data Sheet

## MAK METAMOL R

ISO VG: 100 & 220

NON ISO VG: 181

**DESCRIPTION**  
 These are specially made by blending mineral and fatty oils to give non-drip characteristics and also fortified with carefully selected additives.

**PERFORMANCE BENEFITS**

- Exhibits extreme pressure properties
- possesses rust preventive properties

**APPLICATIONS**  
 This oil is specially designed to meet the lubrication requirements of percussion type pneumatic tools in general and rock drills in particular, where lubrication requirements are very critical.

**PERFORMANCE LEVEL**

- Proprietary grade

Characteristics	IS 1448	Typical Figures		
		100	181	220
Appearance	--	Bright & Clear	Bright & Clear	Bright & Clear
Density at 15°C	P:16	0.9100	0.9393	0.9443
Viscosity Index	P:56	99	96	94
K.V at 40°C, cSt	P:25	100.1	181.2	220.5
Flash Point, (COC), °C	P: 69	240	250	260
Pour point, °C	P: 10	-6	-6	-6

**Health and Safety**

These oils are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

**Bharat Petroleum Corporation Ltd.**  
 Technical Services  
 A<sup>1</sup> Installation, Sewree (East), Mumbai – 400 015  
 Phone: 022-24176354, Fax: 022-24182511 / 24166512  
 email: z\_techservices@bharatpetroleum.in

Edition: R&D / Indl / 098 / Issue 1 / Oct, 2008