

Product Data Sheet

MAK FREEZOL J

ISO VG: 100

DESCRIPTION

This is specially blended compounded oil of relatively low viscosity from Naphthenic type base oil.

PERFORMANCE BENEFITS

- Better lubricity

APPLICATIONS

It is recommended for cylinder lubrication of reciprocating compressors where moisture conditions warrant the use of compounded oil.

PERFORMANCE LEVEL

- Proprietary grade

Characteristics	IS 1448	Typical Figures
Appearance	--	Bright & Clear fluid
Density at 15°C	P:16	0.8976
K.V at 40° C, cSt	P:25	100.1
Viscosity Index	P:56	58
Pour Point, °C	P:10	-27
Flash Point, (COC), °C	P:69	216
Copper Strip Corrosion Test at 100°C for 3 hrs.	P:15	1a

Health and Safety

This oil is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A' Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Indl / 108 / Issue 1 / Oct, 2008