

Product Data Sheet

MAK METAMOL R

ISO VG: 100 & 220

NON ISO VG: 181

DESCRIPTION

These are specially made by blending mineral and fatty oils to give non-drip characteristics and also fortified with carefully selected additives.

PERFORMANCE BENEFITS

- Exhibits extreme pressure properties
- possesses rust preventive properties

APPLICATIONS

This oil is specially designed to meet the lubrication requirements of percussion type pneumatic tools in general and rock drills in particular, where lubrication requirements are very critical.

PERFORMANCE LEVEL

- Proprietary grade

Characteristics	IS 1448	Typical Figures		
		100	181	220
Appearance	--	Bright & Clear	Bright & Clear	Bright & Clear
Density at 15°C	P:16	0.9100	0.9393	0.9443
Viscosity Index	P:56	99	96	94
K.V at 40°C, cSt	P:25	100.1	181.2	220.5
Flash Point, (COC), °C	P: 69	240	250	260
Pour point, °C	P: 10	-6	-6	-6

Health and Safety

These oils are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A¹ Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Indl / 098 / Issue 1 / Oct, 2008