

# Gulfcut 56A Non-staining Neat Cutting Oil

## **Product Description**

**Gulfcut 56A** is premium quality neat cutting oil developed for severe machining operations. This product is formulated with extreme-pressure additives to protect tool and work-piece over a wide range of operating conditions. This oil is formulated with specially treated base oils with less sensitivity to the skin in case of incidental contact to the operator.

### **Features & Associated Benefits**

Features	Associated Benefits	
High quality extreme pressure additives	Long life of tool and protection of work-piece	
Low viscosity	Effective lubrication	
Non-reactivity to metal surfaces	No discoloration of work-piece and tool	
Light Colour	Visibility to the operator	

## **Applications**

- Teeth grinding, Gear Shaving
- Gear generation operations with complicated profiles
- · Machining operations with high severity

**Specifications & Typical Properties** 

Specification Specification		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Kinematic Viscosity at 40°C, cSt	D 445	13.5
Flash Point, °C, COC	D 92	155
Density @ 15 °C Kg/l	D 1298	0.8981
Copper Corrosion	D130	1b
Active Sulphur		Absent
Chlorine		Absent

**Material Compatibility** 

Ferrous Metals	Yes	Ceramic	Yes
Yellow Metals	Yes	Diamond	Yes
Alloys of	Refer to Gulf Oil	Boron Nitride	Yes
Aluminium	Representative		

### Handling & Storage guidelines

- Refer Safety Data Sheets for Health and Safety related information.
- Used product to be disposed by referring to applicable statutory guidelines.
- Store preferably in in-door condition.
- Under normal storage conditions, the product should be consumed within 1 year for optimum performance.

August 2014