



LUBRICANTS™

POWER TO PERFORM™

HP GEAR OIL XP 80W, 90, 140

DESCRIPTION

HP GEAR OIL XP are multipurpose gear oils containing extreme pressure additives for moderate as well as severe condition service

APPLICATIONS

Application areas are hypoid differential & drive axles and manual transmissions of automobiles

MEETS REQUIREMENTS OF

- API GL-5
- MIL-L- 2105 C
- EP type GL-5 level of IS: 1118:1992 (Re-affirmed 2011) specifications

FEATURES & BENEFITS

- Excellent thermal & chemical stability
- Protection against rust & corrosion ensuring longer trouble free protection
- Good performance even under extreme pressure & varying load conditions

PHYSICO-CHEMICAL PROPERTIES (TYPICAL)

| HP GEAR OIL XP | 80W | 90 | 140 |
|--|-------------|--------|-----------|
| Kinematic Viscosity, @ 100°C, cSt | 10.5 - 12.5 | 17- 18 | 24 – 32.5 |
| Viscosity Index | 90 | 94 | 93 |
| Flash Point, (COC), °C | 165 | 230 | 240 |
| Pour Point, °C | -21 | -9 | -9 |
| Corrosion, Copper Strip, At 121°C For 3 Hours, Max | 3 | 3 | 3 |