

HP GEAR OIL XP 85W 140 (T2)

Premium Gear Oil for Hypoid Differentials, Rear Axles And Final Drives

DESCRIPTION

HP GEAR OIL XP 85W 140 (T2) grade is a premium quality extreme pressure type multi-grade automotive gear oil specifically designed to address the requirements of gears, particularly hypoid gears in passenger cars and other automotive equipment operated under high-speed, shock-load; high-speed, low-torque; and low-speed, high-torque conditions.

APPLICATIONS

HP GEAR OIL XP 85W 140 (T2) grade is recommended for the new generation vehicles for heavy duty service in their differentials, rear axles, live front axles and final drives.

PERFORMANCE BENEFITS

- Excellent protection to gear components against wear under heavy loads
- Permits operation across broad temperature range
- Fuel Economy
- Longer oil and component life

MEETS REQUIREMENTS OF

- API GL-5
- MIL-L- 2105 D
- EP type GL-5 level of IS: 1118:1992 (Re-affirmed 2011) specifications

PHYSICO-CHEMICAL PROPERTIES (TYPICAL)

Kinematic Viscosity @ 100°C, cSt	24-28
	24-20
Viscosity Index	90
Flash Point, COC,°C	210
Pour Point, °C	-12
Phosphorus, % wt	0.088 - 0.108